



HAND INSPECTION LAMP 24V/230V

Inspection lamp for working process checks. Completely insulating self-extinguishing rubber construction, abrasion resistant, non-inflammable and single fluid resistant:

Fuel Jet-A1

Specification DERD 2494

Skidrol Oil

Specification BMS 3 - 11

Univis Oil

Specification MIL - H - 5608

Concentrated or diffused beam reflector in ultrapure polished and anodised aluminium. Complete with lampholder for universal connection (GY6,35/G4). Tempered glass lens 5mm thick, protected by rubber buffer. Thumb switch with three positions ON-OFF-MOMENTARY ON, protected by rubber cap mounted on a special circular seat, guaranteeing a perfect seal against dust and liquids. Steel suspension hook for wall or ceiling fixing. Triple clamped cable protection tang to resist cable damage.

Supply voltages 42V - 48V on request.

POWER W	VOLTAGE V	SPIRAL CABLE	FLYING PPLUG	BEAM	ARTICLE NO.
20	24	4m 2x1mmq	CEE P17 16A 2P 24V	FLOOD	116032520 S
20	24	4m 2x1mmq	CEE P17 16A 2P 24V	SPOT	115032520 S
50	24	4m 2x1mmq	CEE P17 16A 2P 24V	FLOOD	116052520 S
50	24	4m 2x1mmq	CEE P17 16A 2P 24V	SPOT	115052520 S
50	230	4m 2x1mmq	CEE P17 16A 2P+T 230V	FLOOD	116055550 S
50	230	4m 2x1mmq	CEE P17 16A 2P+T 230V	SPOT	115055550 S

ID55