



LED lamp with flexible arm.

- Removable magnetic head allows a great versatility of use (up to two meters)
- 1 power LED 3W source
- 8°-25°-40°-60° lens
- External LED driver
- 230V 50/60Hz or 24Vdc Power Supply
- Operating current: 700mA (use ONLY DC stabilized power supplies!)

Electrical features

Power Supply	230V 50/60Hz - 24Vdc
LED driver 700mA	Separated LED driver
IEC class	II(230V) - III(24Vdc)

Optical and mechanical features

LED type	Power led
LED lifetime	50 000 h
Lens	8°-25°-40°-60°
Light color	5000K - CRI75
Structure	Anodized aluminum
Coverage	Tempered glass sp.4mm
Protection index	IP65 (spot)
Lamp color	Black
Working temperature	-20 +55°C
Fastening	Screws / Clamp 04 / Magnetic base B02
Power cable	Neoprene cable 2x0,35mmq L1,5m

Model	Power Supply	N. of LED	Power Watt	Lumen led	Driver	Weight
BF1TMA.XX.24	24 Vdc	1	3W	170 lm	A0321105070818B	1,40 Kg / 3,09 lb
BF1TMA.XX.230	230 V 50/60Hz	1	3W	170 lm	A0481005060806B	1,40 Kg / 3,09 lb

DIMENSIONS (all values in millimeters / inch)

