



Led lamp for industrial machines, CNC and EDM machines.  
 Anodized aluminum structure with diffusing glass 5mm thick.  
 New led technology with Integrated Driver System (IDS).  
 High efficiency white homogeneous light.  
 Easy to install. Easily adjustable thanks to the innovative mounting system.  
 Power supply 24Vdc - M12 4P (M) connection.  
 Four sizes available.

*Particularly suitable for high speed milling machines, CNC, extreme working environments.  
 It can be installed also in wet environments.*

## 24VDC VERSION – Electrical features

Model	Power supply	Nr di LED	Watt	Current	Light color	Beam	Weight
TRACKALPHA.2.50	24 VDC	36	13 W	0,6 A	5000 K - CRI75	120°	1,15 Kg ~
TRACKALPHA.5.50	24 VDC	90	34 W	1,5 A	5000 K - CRI75	120°	2,20 Kg ~
TRACKALPHA.7.50	24 VDC	126	47 W	2,1 A	5000 K - CRI75	120°	3,25 Kg ~
TRACKALPHA.10.50	24 VDC	180	68 W	3,0 A	5000 K - CRI75	120°	4,50 Kg ~

## Structure

Heatsink	extruded aluminum anodized
Side caps	painted aluminum
Frontal glass	tempered 5mm thick
Diffuser	internal glazed diffuser
Index of protection	IP67
Operating temperature	-20 / +55°C

## DIMENSIONS (all values in millimeter)

