

## Series LWS

Bright, vibration resistant long life fluorescent tube.  
 180° light fitted with anti-glare grid.  
 Built in high frequency electronic ballast  
 Borosilicate glass tube  
 Class III (24v) Class II (110v & 230V)  
 Sealed to IP67



Please note that the below fittings are only a small selection of this Series of fittings.  
 Please contact us for details of the complete range.

Power (W)	Luminous flux (Lumen)	Dimensions (mm)			Voltage (V)	Article n° 180° with grid	Article n° 180°	Article n° 360°
		A	B	C				
13	800	267	202	115	24V ac	LWSN20001	LWSN20000	LWSN20002
					24V dc	LWSN90001	LWSN90000	LWSN90002
					110V ac	LWSN30001	LWSN30000	LWSN30002
					230V ac	LWSN50001	LWSN50000	LWSN50002
18	1200	288	223	137	24V ac	LWSR20001	LWSR20000	LWSR20002
					24V dc	LWSR90001	LWSR90000	LWSR90002
					110V ac	LWSR30001	LWSR30000	LWSR30002
					230V ac	LWSR50001	LWSR50000	LWSR50002
26	1800	300	235	149	24V ac	LWST20001	LWST20000	LWST20002
					24V dc	LWST90001	LWST90000	LWST90002
					110V ac	LWST30001	LWST30000	LWST30002
					230V ac	LWST50001	LWST50000	LWST50002