



Slim linear LED. Lamp for small and medium industrial machines. Solid anodized aluminum structure with protective glass 4mm depth. High-efficiency 6W multi-chip LED. I.D.S. technology for 24VDC connection. Shockproof and vibrations resistant. Four versions available: 6-12-18-24W Power supply 24VDC.

LED source exempt from photobiological risk.

Electrical features

Power supply	24 Vdc
LED driver 700mA dc cost	integrato
IEC class	III
Degree of protection	IP67
Connection	cable /conn M12 4P(Male) only external version

Optical and mechanical features

LED type	LED multichip
LED lifetime	50 000 h
Brightness	wide beam 120°
Light color	5000K Ra65
Structure	Anodized aluminum
Covering	tempered glass 4mm
Colore lampada	Aluminum
Operating temperatur	-20 +55°C
Fastening	M5 screws
Power cable	H05RN-F Neopren 2x0,75mmq: brown (+24Vdc) – blue (-24Vdc)

Model	Power supply	N° LED	Current	Watt	Light color	Weight
EXLIGHT.6.x	24Vdc	1	700mA	6 W	5000 K	0,50 Kg ~
EXLIGHT.12.x	24Vdc	2	700mA	12 W	5000 K	0,90 Kg ~
EXLIGHT.18.x	24Vdc	3	1400mA	18 W	5000 K	1,30 Kg ~
EXLIGHT.24.x	24Vdc	4	1400mA	24 W	5000 K	1,70 Kg ~

DIMENSIONS (all values in millimeter)

