

AuLED 20

System of protection	IP67
Series	surface lamp
Dimension	22 x 90 x 540 mm
Cover plate	ESG - glass = toughened safety glass
Power	25 W
Voltage	24 V/DC
Luminous	2300 Lumen
Item nos.	592-502-001 (M8-plug side) 592-502-002 (M8-plug behind) 592-502-011 (M12-plug side) 592-502-012 (M12-plug behind)

CHARACTERISTICS / ADVANTAGE

- very robust Al-box
- toughened safety glass
- plug connection M8 or M12 behind or at side
- IP 67 / 69 K
- glass cover and LED board can be easily exchanged



AuLED 20



TYPE	COVER PLATE	ITEM NO.	POWER	LUMINOUS	DIMENSION / MM	VOLTAGE	PLUG
AuLED 20	ESG	592-502-001	25 W	2300	22 x 90 x 540	24 V/DC	M8-side
AuLED 20	ESG	592-502-002	25 W	2300	22 x 90 x 540	24 V/DC	M8-behind
AuLED 20	ESG	592-502-011	25 W	2300	22 x 90 x 540	24 V/DC	M12-side
AuLED 20	ESG	592-502-012	25 W	2300	22 x 90 x 540	24 V/DC	M12-behind

ACCESSORIES



Power supply stabilized
 Power: 30 W
 Item no.: 213-820-208
 Voltage: 100-240 V / 50-60 Hz /
 24 V/DC

DRAWING

