



Compact LED lamp.

- Spot 3-6-9 led.
- Short arm.
- Narrow, medium and wide beam angle.
- Integrated LED driver (IDS System).
- 24 Vdc Power Supply.

### Electrical features


Power supply	24Vdc
LED driver 500mA	Integrated driver (IDS System)
IEC class	III

### Optical and mechanical features

LED type	Power led
LED lifetime	50 000 h
Lens	8°-25°-40°; 60° BC9 only
Light color	5000K - CRI75
Structure	Aluminum
Coverage	Tempered front glass sp.4mm
Protection index	IP65 (spot)
Switch	on/off on the spot
Lamp color	Black
Working temperature	-20 +55°C
Fastening	Screws / Clamp 04 / Magnetic base B02
Power cable	H05RNF 2x0,75mmq Neoprene cable L1,5m

Model	Power Supply	N. of LED	Power Watt	Lumen led	Driver	Weight
BC3.XX.24	24 Vdc	3	6W	450lm	IDS System	0,90 Kg / 1.98 lb ~
BC6.XX.24	24 Vdc	6	12W	900lm	IDS System	0,90 Kg / 1.98 lb ~
BC9.XX.24	24 Vdc	9	18W	1350lm	IDS System	1,25 Kg / 2.76 lb ~

### DIMENSIONS (all values in millimeters / inch)



Model	A – mm/in	B – mm/in
BC3.XX.230	64 / 2.52	86 / 3.39
BC6.XX.230	64 / 2.52	86 / 3.39
BC9.XX.230	90 / 3.54	101 / 3.98



## Compact LED lamp.

- Spot 3-6-9 led.
- Short arm.
- Narrow, medium and wide light beam.
- Separated LED driver.
- 230V 50/60Hz Power Supply.
- Dimmable versions available.

**Electrical features**

Power supply  
 LED driver 500mA, LED driver 350 mA (BF9)  
 IEC Class


230V 50/60Hz  
 Separated LED driver  
 II (with driver)

**Optical and mechanical features**

LED type  
 LED lifetime  
 Lens  
 Light color  
 Structure  
 Coverage  
 Protection index  
 Switch  
 Lamp color  
 Working temperature  
 Fastening  
 Power cable

Power led  
 50 000 h  
 8°-25°-40°; 60° BC9 only  
 5000K - CRI75  
 Aluminum  
 Tempered front glass sp.4mm  
 IP65 (spot)  
 on/off on the spot  
 Black  
 -20 +55°C  
 Screws / Clamp 04 / Magnetic base B02  
 PVC L1,5m with euro plug

Model	Power Supply	N. of LED	Power Watt	Lumen led	Driver	Weight
BC3.XX.230	230V 50/60 Hz	3	6W	450lm	A0181005060705B	0,90 Kg / 1.98 lb ~
BC6.XX.230	230V 50/60Hz	6	12W	900lm	A0141005060709B	0,90 Kg / 1.98 lb ~
BC9.XX.230	230V 50/60Hz	9	18W	1350lm	A0151005060713B	1,25 Kg / 2.76 lb ~

**DIMENSIONS (all values in millimeters / inch)**

Model	A – mm/in	B – mm/in
BC3.XX.230	64 / 2.52	86 / 3.39
BC6.XX.230	64 / 2.52	86 / 3.39
BC9.XX.230	90 / 3.54	101 / 3.98