



Industrial Red Line Laser.
The laser pointers have been designed and built for the alignment and the positioning of materials on sewing and pressing machines as well as for infinite other use.

FEATURES

Code	GRAY12
Operating Voltage	2,6 ~ 5 Vdc
Power	12 mW
Operating current	< 100mA
Laser class	II
Wavelength	645 - 665
Lens	Quartz cylindric
Collimating lens	Glass (Ø6,5mm)
Emitting angle	>90°
Light colour	red
Marking	Line
Width of laser line	3 ±0,5mm @5m - 6 ±0,5mm @10m
Mean time to failure at 20mW 25°C	10.000 H/STD
Case	Ø25x100mm aluminum
Degree of protection	IP65
Power cable	PVC L1,5m with jack
Weight	0,20 Kg ~

PSU

Code	AGRAY20
Vin:	230 Vac 50-60 Hz
Vout:	9 Vdc
Iout:	100 mA (n.2 out)
P:	20 mW
Power cable	PVC L1,5m with europlug
Weight	0,30 Kg ~

Focus distance and line length

	1,00 m	2,00 m	3,00 m	4,00 m	5,00 m
Distance	1,00 m	2,00 m	3,00 m	4,00 m	5,00 m
Lenght	150 cm	310 cm	450 cm	550 cm	700 cm

Hologram



Line

Fastening accessories



Art.36